



SAQ
SIAT

**TECHNICAL SPECIFICATION
BRIGHT DRAWN WIRE**

Document
Revision
Date
Page

SPS101
02 i
18.09.2014
1/2

1. DESCRIPTION.

High quality bright drawn steel wire, according to following standards:

- EN ISO 16120-2 C4D
- EN ISO 16120-2 C7D
- EN ISO 16120-2 C9D
- EN 10277-2.

2. CHEMICAL COMPOSITION ON PRODUCT

Limits	C %	Mn %	Si %	P %	S %
min	-	-	-	-	-
max	0.17	0.50	0.30	0.040	0.040

NOTE:

Materials for hot zinc galvanising available on request.
Materials with lower carbon percentage available on request.

3. MECHANICAL AND DIMENSIONAL PROPERTIES

Ø mm	Toll. mm	RM MPa
1,60 ÷ 2,99	h9-h11	600-950
3,00 ÷ 7,99	h9-h11	500-800
8,00 ÷ 14,00	h9-h11	450-700

4. STANDARD PACKAGING

Packaging coil	Weight Kg.	Nominal dimensions (mm)	
		Int D.	H
1,60÷14,00	700-1500	500/540/600	500

NOTE

Coils strapped at 4 points with 3/4" metallic strap with metal seals

On request:

Coils on 2 wood sticks size 80x80 mm or 100x100 mm

Coils protected with plastic coating

Coils with metallic/cardboard internal tube strapped at 4 points with 3/4" metallic strap with metal seals

Wire on metal spiders

5. LABELLING.

Standard SIAT barcode label reporting:

heat nr. – coil nr. - customer name – date of production – size – weight.

6. STANDARD CERTIFICATION.

In accordance to EN 10204 2.2

Certification EN 10204 3.1 on request.

